

|   |          |              |              |
|---|----------|--------------|--------------|
| TRANSMITTAL SLIP  |          |              | TE           |
| TO: <i>[Signature]</i>  |          |              | <i>4 Aug</i> |
| ROOM NO.  | BUILDING | CONFIDENTIAL |              |
| REMARKS:  |          |              |              |
| <p><i>[Redacted] advised me</i><br/> <i>on 3 Aug that [Redacted]</i><br/> <i>approved installing inciner-</i><br/> <i>ator in [Redacted] office.</i><br/> <i>So let's get on with it.</i><br/> <i>Getting instructions to</i><br/> <i>GSA to make necessary modifi-</i><br/> <i>cations to [Redacted] office for</i><br/> <i>acceptance with Safety</i></p> |          |              |              |
| FROM: <i>Walt</i> (over)  |          |              |              |
| ROOM NO.  | BUILDING | EXTENSION    |              |

25X1

25X1

25X1

officer's recommendations  
and what ~~has to be~~  
is necessary for  
proper operation is  
probably your first order  
of business.

~~CONFIDENTIAL~~  
To be used if needed  
[redacted] - says we  
can use his office ( [redacted] ) voices  
no objections except for minor  
modifications if we can get  
[redacted] approval.  
WE

25X1  
25X1

25X1

~~SECRET~~*file:  
Air-Fed Incinerator*D  
R  
A  
F  
T

CONFIDENTIAL

29 July 1960

MEMORANDUM FOR: Chief, TSD/Support Staff

SUBJECT : Placement of Model 2 Air-Fed Incinerator

1. The first prototype Model 2 Air-Fed Incinerator has been completed and is presently sitting at the receiving deck [redacted]

25X1

[redacted] This model incinerator has been brought in to the headquarters area in order to be set up in an office for demonstration and test purposes.

25X1

2. This incinerator is 64 inches high (not including the stack) and 24 inches outside diameter. A 220 volt, 3 phase, 60 cycle, 1½ HP electric motor is located in the bottom section of the unit which enables the operator to destroy between 75 and 125 pounds of classified paper files per hour. A 9 inch diameter stack protrudes from the top of the incinerator which must be outletted from the room or building to enable the hot combustion gasses to be exhausted. A room at least 8 feet square and ten feet high is desirable for the installation of this incinerator.

3. It is requested that a room be selected for the placement of this prototype Model 2 Air-Fed Incinerator. If further information is requested please contact the undersigned or the project engineer for this program,

25X1

|               |                   |               |
|---------------|-------------------|---------------|
| DOC 21        | REV DATE 07/20/60 | BY 010936     |
| ORIG COMP 056 | CHI 06            | TYPE 02       |
| ORIG CLASS 5  | PAGES 3           | REV CLASS 2   |
| DATE 07-27    | NEXT REV 2010     | AUTH: MR 70-2 |

Chief

TSD/Engineering Branch

25X1

:nt

CONFIDENTIAL

~~SECRET~~